

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织  
国际局



(43) 国际公布日:

2005年3月31日(31.03.2005)

PCT

(10) 国际公布号:

WO 2005/029134 A1

(51) 国际分类号: G01W 1/14, G01N 27/22

(21) 国际申请号: PCT/CN2004/000682

(22) 国际申请日: 2004年6月24日(24.06.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:  
03160008.5 2003年9月19日(19.09.2003) CN  
03160009.3 2003年9月19日(19.09.2003) CN

(71)(72) 发明人/申请人: 孙滕谔(SUN, Tengchen) [CN/CN];  
中国北京市朝阳区光华里15号楼351号, Beijing  
100020 (CN)。于杰(YU, Jie) [CN/CN]; 中国北京市西  
城区德内大街延年胡同3号, Beijing 100020 (CN)。

(74) 代理人: 北京金之桥知识产权代理有限公司(BEIJING  
GOLDEN-BRIDGE IP AGENCY CO., LTD) 中国北  
京市海淀区知春路49号希格玛公寓A座108室, Beijing  
100080 (CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护):  
AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,

BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM,  
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NA, NL, NO, NZ, OM, PG, PH, PL,  
PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护):  
ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD,  
SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY,  
KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG,  
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,  
IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR),  
OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG)


本国际公布:

— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期  
PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A DEVICE AND METHOD FOR DETECTING THE ENVIRONMENT CHANGE OF WINDSHIELD

(54) 发明名称: 一种检测汽车挡风玻璃环境变化的装置及方法



(57) Abstract: A device for detecting the environmental change of a windshield comprises a plane capacitor which is disposed on the inner surface of the windshield, two electrodes of said plane capacitor are disposed on the same surface, the area of the two electrodes is less than 100 sq.centimetres, said plane capacitor is a sense element which detects the environmental change of windshield and the environmental change after operating, said plane capacitor is electrically connected to a sensor detection circuit, the change signal in capacitance which is affected by the environment is transmitted to said sensor detection circuit, said sensor detection circuit is responsive to the change of capacitance to produce a control signal which controls the device. The structure of this device is simple, the known photoelectric capacitor and a plan capacitor detection device have disadvantages that the measure area is small and the installation is difficult, they can not measure the thickness of rain and be easy to be affected by dirt, they have poor adaptability and the cost is high, said device can solve above-described problems.

[见续页]

WO 2005/029134 A1